

Oscilla[®] SM910 Screening audiometer



* Pulse tone *
* Easy to operate *

SPECIAL FEATURES

Pulse tone
Noise free push buttons.
Very readable displays.
11 frequencies: 125 Hz - 8000 Hz.
Calibration without entering the cabinet.

Oscilla® SM910 Screening audiometer is a modern manual audiometer, which you may learn to operate within a few seconds.

Design as well as advanced technology has been enforced, and by means of processor controlled technique, the **Oscilla® SM910 Screening audiometer** is still made for the future. For the tone generator is used technology, which assures a 100% stable tone without any delay or distortion.

Aluminium cabinet provides you with a neat product, which at the same time is very sturdy and protects in the best way against any environmental influences from other electronic equipment; as aluminium protects in a far better way than say plastics.

Technical specifications:

Frequencies : 11 frequencies from 125 Hz to 8000 Hz.
Hearing Level Range : -10 dB to 90 dB in 5 dB increments.

Maximum intensities:

Frequencies Hz	125	250	500	750	1000	1500	2000	3000	4000	6000	8000
Air conduction dB	50	70	90	90	90	90	90	90	90	80	70

Program : Manual test.
Calibration : Calibration data stored in programmable memory (EN60645-1).
Power supply : Adapter 12V AC (220-240V).
Dimensions : 225mm x 180mm x 55mm.
Weight : 650 g (unit only).
Standard accessories : TDH-39 earphones, SILENTA noise reducing headset, patients button, adapter.
Optional extras : Carrying bag.